

MTA-4-06HT-E-KV-D OFNR BK

Part Number: **F40060638B**

Applications:

Backbone and Riser cabling, Centralized Cabling, General purpose armored Indoor/Outdoor, General purpose indoor LAN, Suitable for installation in ducts and trays, Short and Medium distance distribution and trunking

General Construction:

The cable consists of 6 multi-mode 50/125 OM3 optical fibers each with a 0.9 mm tight buffer. The color coded buffered fibers are stranded together to form the cable core. The cable is reinforced by a dielectric strength yarns and protected with a jacket. The cable is designed to comply with UL OFNR.



Outer Jacket Material:

FR-PVC

Outer Diameter:

4.8 mm nom.

Weight:

26 kg/km

Design & Materials

Buffer Material:	FR-LSZH
Buffer Diameter:	900 µm
Strength Elements:	Aramid Yarns
Number of fibers:	6
Waterblocking:	Dry Waterblocking
Rip-Cord:	Yes
Outer Jacket Color:	Black
Marking:	Per request

Standards

Applicable Standards:	IEC 60794-1-21/22, IEC 60794
Installation:	Guidelines as per IEC TR 62691

Performance

Max. Installation Tensile Load :	660 N max.
Max. Residual Tension (MRS) :	350 N max.
Impact Resistance:	5 N*m
Impact Resistance:	3 cycles
Max. Crush Resistance:	180 N/cm
Min. Bend Radius for Installation:	20xD mm
Min. Bend Radius for Operation:	10xD mm
Repeated Bending:	300 cycles
Torsion (L=125 x d):	10 cycles
Max. Operating Temperature:	+85 °C
Min. Operating Temperature:	-40 °C
Max. Installation Temperature:	+45 °C
Min. Installation Temperature:	-10 °C
Max. Storage Temperature:	+85 °C
Min. Storage Temperature:	-55 °C
UV Resistance:	Yes
Waterblocking:	Yes

Prepared By	Revised By	Version Num	Modified on
Olga Kirshner	David Miller	1.3	08-08-2018

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500
6770650

ISRAEL

Tel: +972 4 6770555

Fax: +972 4